



11/02/00

A


IN THE UNITED STATES PATENT AND TRADEMARK OFFICE


CERTIFICATE OF EXPRESS MAILING

I hereby certify that this paper and the documents and/or fees referred to as attached therein are being deposited with the United States Postal Service on October 31, 2000 in an envelope as "Express Mail Post Office to Addressee" service under 37 CFR §1.10, Mailing Label Number **EL580854123US**, addressed to the Assistant Commissioner for Patents, Washington, DC 20231.

Attorney Docket No.: SUN1P814/P5417

First Named Inventor: SOKOLOV




Mandy Franklin

UTILITY PATENT APPLICATION TRANSMITTAL (37 CFR. § 1.53(b))

Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231

Sir: This is a request for filing a patent application under 37 CFR. § 1.53(b) in the name of inventors:
Stepan SOKOLOV, David WALLMAN

For: **IMPROVED FRAMEWORKS FOR LOADING AND EXECUTION OF OBJECT-BASED PROGRAMS**

Application Elements:

- ☒ 23 Pages of Specification, Claims and Abstract
- ☒ 08 Sheets of formal Drawings
- ☒ 02 Pages Combined Declaration and Power of Attorney

Accompanying Application Parts:

- ☒ Assignment and Assignment Recordation Cover Sheet (recording fee of \$40.00 enclosed)
- ☐ 37 CFR 3.73(b) Statement by Assignee
- ☐ Information Disclosure Statement with Form PTO-1449
- ☐ Copies of IDS Citations
- ☐ Preliminary Amendment
- ☒ Return Receipt Postcard
- ☐ Small Entity Statement(s)
- ☐ Other:

Fee Calculation (37 CFR § 1.16)

	(Col. 1) Total Claims		(Col. 2) Claims	(Col. 3) Present Extra	Rate	Additional Fee
TOTAL	28	MINUS	20	= 08	x 18	144.00
INDEP.	04	MINUS	3	= 01	x 80	80.00
[] First presentation of multiple dependent claim					\$270	
Basic Filing Fee under 37 C.F.R. §1.16(a)					\$710	710.00
TOTAL						710.00
SMALL ENTITY 50% FILING FEE REDUCTION (if applicable)						934.00

☒ Check No. 9428 in the amount of \$974.00 is enclosed.

☒ The Commissioner is authorized to charge any fees beyond the amount enclosed which may be required, or to credit any overpayment, to Deposit Account No. 500388 (Order No. SUN1P814).

General Authorization for Petition for Extension of Time (37 CFR §1.136)


☒ Applicants hereby make and generally authorize any Petitions for Extensions of Time as may be needed for any subsequent filings. The Commissioner is also authorized to charge any extension fees under 37 CFR §1.17 as may be needed to Deposit Account No. 500388 (Order No. SUN1P814).

☒ Please send correspondence to the following address:

Customer Number 022434
BEYER WEAVER & THOMAS, LLP
P.O. Box 778
Berkeley, CA 94704-0778
Telephone (650) 961-8300
Fax (650) 961-8301



Date: 10/31/2000



Ramin Mahboubian
Registration No. 44,890

PATENT APPLICATION

**IMPROVED FRAMEWORKS FOR LOADING AND EXECUTION OF OBJECT-
BASED PROGRAMS**

- Inventors:
1. Stepan SOKOLOV
34832 Dorado Common
Fremont, CA 94555
Citizen of Ukraine
 2. David WALLMAN
777 S. Mathilda Ave. #266
Sunnyvale, CA 94087
Citizen of Israel

Assignee: Sun Microsystems, Inc.
901 San Antonio Road
M/S PAL01-521
Palo Alto, CA 94303

BEYER WEAVER & THOMAS, LLP
P.O. Box 778
Berkeley, CA 94704-0778
Telephone (650) 961-8300

IMPROVED FRAMEWORKS FOR LOADING AND EXECUTION OF OBJECT-BASED PROGRAMS

5

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is related to U.S. Patent Application No. _____
(Att.Dkt.No. SUN1P809/P5500), entitled "IMPROVED FRAMEWORKS FOR
INVOKING METHODS IN VIRTUAL MACHINES", filed concurrently herewith,
10 and hereby incorporated herein by reference.

This application is related to U.S. Patent Application No. _____
(Att.Dkt.No. SUN1P810/P5510), entitled "IMPROVED METHODS AND
APPARTUS FOR NUMERIC CONSTANT VALUE INLINING IN VIRTUAL
MACHINES", filed concurrently herewith, and hereby incorporated herein by
15 reference.

BACKGROUND OF THE INVENTION

The present invention relates generally to object-based high level
20 programming environments, and more particularly, to frameworks for loading
and execution of portable, platform independent programming instructions
within a virtual machine.

Recently, the Java™ programming environment has become quite
popular. The Java™ programming language is an language that is designed to be
25 portable enough to be executed on a wide range of computers ranging from
small devices (e.g., pagers, cell phones and smart cards) up to supercomputers.
Computer programs written in the Java programming language (and other
languages) may be compiled into Java virtual machine instructions (typically
referred to as Java bytecodes) that are suitable for execution by a Java virtual
30 machine implementation.

The Java virtual machine is commonly implemented in software by means
of an interpreter for the Java virtual machine instruction set but, in general, may
be software, hardware, or both. A particular Java virtual machine

implementation and corresponding support libraries, together constitute a Java™ runtime environment.

Computer programs in the Java programming language are arranged in one or more classes or interfaces (referred to herein jointly as classes or class files). Such programs are generally platform, i.e., hardware and operating system, independent. As such, these computer programs may be executed, unmodified, on any computer that is able to run an implementation of the Java™ runtime environment. A class written in the Java programming language is compiled to a particular binary format called the “class file format” that includes Java virtual machine instructions for the methods of a single class. In addition to the Java virtual machine instructions for the methods of a class, the class file format includes a significant amount of ancillary information that is associated with the class. The class file format (as well as the general operation of the Java virtual machine) is described in some detail in The Java Virtual Machine Specification by Tim Lindholm and Frank Yellin (ISBN 0-201-31006-6), which is hereby incorporated herein by reference.

Conventionally, when a class file is loaded into the virtual machine, the virtual machine essentially makes a copy of the class file for its internal use. The virtual machine’s internal copy is sometimes referred to as an “internal class representation.” In conventional virtual machines, the internal class representation is typically almost an exact copy of the class file and it replicates the entire Constant Pool. This is true regardless of whether multiple classes loaded into the virtual machine reference the same method and thus replicate some (or much) of the same Constant Pool information. Such replication may, of course, result in an inefficient use of memory resources. In some circumstances (particularly in embedded systems which have limited memory resources) this inefficient use of memory resources can be a significant disadvantage.

As described in The Java Virtual Machine Specification, one of the structures of a standard class file is known as the “Constant Pool.” The Constant Pool is a data structure that has several uses. One of the uses of the Constant Pool that is relevant to the present invention is that the Constant Pool contains

the information that is needed to resolve various Java Instructions, for example, a method invocation instruction that can be invoked by any of the methods within the class. Fig. 1A (which may be familiar to those skilled in the art) is a representation of a Constant Pool section of a class file that contains the information necessary to uniquely identify and locate a particular invoked method.

Additionally, conventional virtual machine interpreters decode and execute the virtual machine instructions (Java bytecodes) one instruction at a time during execution, e.g., "at runtime." To execute a Java instruction, typically, several operations have to be performed to obtain the information that is necessary to execute the Java instruction. For example, to invoke a method referenced by a Java bytecode, the virtual machine must make several operations to access the Constant Pool simply to identify the information necessary to locate and access the invoked method.

To illustrate, Fig. 1B shows an exemplary conventional Java bytecode stream 150 including virtual machine instructions (typically referred to as Java bytecodes) that are suitable for execution by a conventional Java virtual machine. The first bytecode, Java bytecode 152 represents an arithmetic Java "Add" command with no associated parameters. The second bytecode, Java bytecode 154 represents a Java "iconst" instruction (load an integer constant on the stack). The Java bytecodes 156 and 157, CP-IndexA and CP-IndexB, respectively represent the first and second bytes of an index to the constant pool for the integer constant. It should be noted that Java bytecodes 152, 154 and 156 collectively represent a Java "iconst" instruction. In order to execute the Java Instruction iconst, at run time, an index to the Constant Pool is constructed from the CP-IndexA and CP-IndexA. Once an index to the Constant Pool has been determined, the appropriate structures in the Constant Pool have to be accessed so that the appropriate constant value can be determined. Accordingly, the Java instruction "iconstant" is executed but only after performing several operations at run time. As can be appreciated from the example above, the execution of a relatively simple instruction such as loading a constant value can take a significant amount of run time.

Furthermore, execution of relatively more complex Java instructions requires even more processing than noted above. For example, in order to conventionally execute an invoke method command 158, the constant pool has to be accessed several times at run time just to obtain the symbolic
5 representation of information associated with the method. The CP_IndexC and CP_IndexD are indexes to a constant pool where information relating to the method including its parameter values needed for execution can be found. Accordingly, a CP_IndexD associated with the method instruction 158 is typically an index to an entry into the Constant Pool wherein that entry itself
10 provides another pair of indexes to other entries in the Constant Pool, and so forth. Thus, execution of an invoke method command would require a significant amount of processing at run time (e.g., accessing the Constant Pool several times to obtain symbolic representation relating to the method). As will be appreciated, this conventional technique is an inefficient approach that may
15 result in significantly longer execution times. In addition, once the symbolic information relating to the method has been obtained, there may be a need to convert the symbolic information into an internal representation at run time. Again, this is an inefficient approach.

Accordingly, there is a need for improved frameworks for loading and
20 execution of portable, platform independent programming instructions within a virtual machine.

SUMMARY OF THE INVENTION

To achieve the foregoing and other objects of the invention, improved frameworks for loading and execution of portable, platform independent programming instructions within a virtual machine will be described. One aspect of the present invention seeks to provide a mechanism that will generally improve the runtime performance of virtual machines by eliminating the need to always traverse a constant pool at runtime to execute a Java instruction. In effect, the described system contemplates doing some extra work during the loading of a class into a virtual machine by obtaining the information from the constant pool during loading and representing that information in a form that can be used more efficiently at runtime.

In other aspects of the invention, specific data structures that are suitable for use within a virtual machine and methods for creating such data structures are described. In one embodiment, an enhanced Java bytecode representation having a pair of Java bytecode streams is disclosed. The enhanced Java bytecode has a Java code stream suitable for storing various Java commands as bytecodes within a code stream. A Java data stream is used to store the data parameters associated with the Java commands in the code stream. As will be appreciated, the invention allows for representation of actual parameter values, or references to actual parameter values, in the code stream. Accordingly, data parameters can be provided for efficient execution of Java instructions without requiring further processing of Constant Pools at run time. As a result, the performance of Java compliant virtual machine can be enhanced.

The invention can be implemented in numerous ways, including a system, an apparatus, a method or a computer readable medium. Several embodiments of the invention are discussed below.

As a method of creating data structures suitable for use by a virtual machine to execute computer instructions, one embodiment of the invention includes converting a stream, having commands and data associated with the commands, into a pair of streams for use in the virtual machine. The pair of

streams includes a code stream and a data stream for data associated with the commands in the code stream.

As a data structure for containing computer executable commands and data associated with the computer executable commands, the data structure
5 suitable for use by a virtual machine in an object oriented programming environment, one embodiment of the invention includes a code portion having one or more computer executable commands, and a data stream having data corresponding to the one or more computer executable commands.

As a method of executing computer instructions on a virtual machine,
10 one embodiment of the invention includes the acts of: fetching a command associated with a computer instruction from a code stream; determining whether the command has an associated parameter; fetching from a data stream the associated parameter of the command when that command has an associated parameter; and executing the command with the associated parameters after the
15 associated parameter of the commands have been fetched.

As a method of creating data structures suitable for use by a virtual machine to execute Java instructions, another embodiment of the invention includes converting a Java bytecode into a pair of Java bytecode streams suitable for use by the virtual machine. The pair of Java bytecode streams being a Java
20 code stream that includes Java commands and a Java data stream that includes the data associated with the commands in the Java code stream.

Other aspects and advantages of the invention will become apparent from the following detailed description, taken in conjunction with the accompanying drawings, illustrating by way of example the principles of the invention.

25

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will be readily understood by the following detailed description in conjunction with the accompanying drawings, wherein
5 like reference numerals designate like structural elements, and in which:

Fig. 1A is a representation of a Constant Pool section of a Java class file.

Fig. 1B shows an exemplary conventional Java bytecode stream including virtual machine instructions.

Fig. 2 is a block diagram representation of Java bytecode streams in
10 accordance with one embodiment of the invention.

Fig. 3 illustrates an execution method for executing Java bytecode instructions in accordance with one embodiment of the invention.

Fig. 4 illustrates an exemplary bytecode stream generation method in accordance with one embodiment of the invention.

Fig. 5 illustrates an exemplary loading method for loading bytecodes of a
15 class file in accordance with one embodiment of the invention.

Fig. 6 illustrates a processing method for processing a Java Load constant command in accordance with one embodiment of the invention.

Fig. 7 illustrates an execution method for executing a Java Load Constant
20 command in accordance with one embodiment of the invention.

DETAILED DESCRIPTION OF THE INVENTION

5 As described in the background section, the Java programming environment has enjoyed widespread success. Therefore, there are continuing efforts to extend the breadth of Java compatible devices and to improve the performance of such devices. One of the most significant factors influencing the performance of Java based programs on a particular platform is the performance
10 of the underlying virtual machine. Accordingly, there have been extensive efforts by a number of entities to provide improved performance Java compliant virtual machines. In order to be Java compliant, a virtual machine must be capable of working with Java classes, which have a defined class file format. Although it is important that any Java virtual machine be capable of handling
15 Java classes, the Java virtual machine specification does not dictate how such classes are represented internally within a particular Java virtual machine implementation.

 The Java class file format utilizes the constant pool construct to store the information necessary to execute a Java instruction at run time. However, as
20 suggested above, traversing the constant pool at runtime to obtain the information necessary to execute Java instructions is not particularly efficient. One aspect of the present invention seeks to provide a mechanism that will generally improve the runtime performance of virtual machines by eliminating the need to always traverse a constant pool at runtime to execute a Java
25 instruction. Accordingly, a significant amount of work is conventionally performed at runtime. In effect, the described system contemplates doing some extra work during the loading of a class into a virtual machine by obtaining the information from the constant pool during loading and representing that information in a form that can be used more efficiently at runtime

30 In other aspects of the invention, specific data structures that are suitable for use within a virtual machine and methods for creating such data structures are described. In one embodiment, an enhanced Java bytecode representation having a pair of Java bytecode streams is disclosed. The enhanced Java

bytecode has a Java code stream suitable for storing various Java commands as bytecodes within a code stream. A Java data stream of the enhanced Java bytecode representation is used to store the data parameters associated with the Java commands in the code stream. As will be appreciated, the invention allows
5 for representation in the code stream of actual parameter values, or references to actual parameter values. Accordingly, data parameters can be provided for efficient execution of Java instructions without requiring further processing of Constant Pools at run time. As a result, the performance of Java complaint virtual machine can be enhanced.

10 Furthermore, if the invention is implemented together with other improvements as described in concurrently filed, co-pending Application No. U.S. Patent Application No. _____ (Att.Dkt.No. SUN1P809/P5500), entitled "IMPROVED FRAMEWORKS FOR INVOKING METHODS IN VIRTUAL
15 MACHINES", the constant pool may not even need to be copied into the virtual machine's in order to invoke methods. Thus, the use of the invention in conjunction with the improved techniques provided as described in U.S. Patent Application No. _____ (Att.Dkt.No. SUN1P809/P5500), entitled "IMPROVED FRAMEWORKS FOR INVOKING METHODS IN VIRTUAL MACHINES" has the potential in many circumstances to even further improve the performance of the
20 virtual machines.

Embodiments of the invention are discussed below with reference to Figs. 2 - 7. However, those skilled in the art will readily appreciate that the detailed description given herein with respect to these figures is for explanatory purposes as the invention extends beyond these limited embodiments.

25 Fig. 2 is a block diagram representation of Java bytecode streams 200 in accordance with one embodiment of the invention. The Java bytecode streams 200 can be, for example, implemented as a data structure embodied in a computer readable medium that is suitable for use by a virtual machine. As shown in Fig. 2, the Java bytecode streams 200 includes a pair of Java bytecode
30 streams, namely, a Java code stream 202 and a Java data stream 204. The code stream 202 includes various Java commands 206, 208, and 210. The code stream 206 represents a Java command A which does not have any parameters

associated with it. On the other hand, code streams 208 and 210 represent respectively Java commands B and C with associated data parameters which are represented in the Java data stream 204. The Java bytecode 212 represents data B which is the data parameters corresponding to the Java command B of Java code stream 202. It should be noted that the Java command B and data B together represent a Java instruction corresponding to a Java command B with its associated data. Similarly, the Java bytecodes 214 and 216 represent respectively data C1 and C2 which collectively represent the data parameters corresponding to the Java command C of Java code stream 202. Accordingly, the Java command C, data C1 and data C2 together represent a Java instruction corresponding to a Java command C with its associate data represented in bytecodes 214 and 216.

As noted above, the Java bytecode 200 streams are suitable for use by a virtual machine. Referring now to Fig. 3, an exemplary execution method 300 for executing Java bytecode instructions is disclosed. The execution method 300 can be used, for example, in conjunction with a pair of Java bytecode streams, for example, the Java code stream 202 and Java data stream 204. Initially, at operation 302, the next command in the code stream is fetched. For example, referring back to Fig. 2, the next command fetched can be the bytecode 206 of the Java code stream 202. Next, at operation 304, a pointer to the Java code stream is incremented to point to the next command in the Java code stream. Referring again to Fig. 2, a pointer to the Java code stream 206 is incremented to point to the next command in the Java code stream, for example, the bytecode 206 (Java command B). Following incrementing the pointer at operation 304, the execution method 300 proceeds to operation 306 where a determination is made as to whether the fetched command has an associated parameter. If it is determined at operation 306 that the fetched command does not have an associated parameter, for example, in the case of Java command A of Fig. 2, the execution method 300 proceeds directly to operation 312 where the fetched command (with no associated parameter) is executed. Thereafter, at operation 314 a determination is made as to whether there are more commands in the Java code stream to execute. If it is determined at operation 314 that there are no

more commands to execute, the execution method 300 ends. However, if it is determined at operation 314 that there is at least one more command to execute, that execution method 300 proceeds back to operation 302 where the next command in the code stream is fetched.

5 On the other hand, if it is determined at operation 306 that the fetched command has an associated parameter, the execution method 300 proceeds to operation 308 where the parameter values associated with the fetched command are fetched from the data stream. Referring back to Fig 2., for example, in the case when the fetched command is the Java command B of bytecode 208, the
10 parameter values associated with Java command B, namely, data B of the bytecode 212 is fetched. Similarly, in the case of the Java command C (bytecode 210), data C1 and data C2 (bytecodes 214 and 216) would be fetched at operation 308. As will be appreciated, the invention allows for parameter values in the data stream which can represent actual parameter values (or
15 references to actual parameter values). Accordingly, the data parameters in the data code can be used to execute instructions without requiring further processing of Constant Pool.

 After the appropriate data is fetched, at operation 310, the pointer to the data command stream is incremented to point to the appropriate position in the
20 data stream. As will be appreciated, the pointer to the data stream can be updated based on the command type (i.e., based on the number of bytecodes appropriated for the data associated with the command). When the command and the appropriate parameter values have been fetched, the execution method 300 proceeds to operation 314 where the fetched command is executed.
25 Finally, at operation 314 a determination is made as to whether there are more commands in the Java code stream to execute. If it is determined at operation 314 that there are no more commands to execute, the execution method 300 ends. However, if it is determined at operation 314 that there is at least one more command to execute, that execution method 300 proceeds back to
30 operation 302 where the next command in the code stream is fetched.

As noted above, the invention, among other things, provides for a pair of Java bytecode streams suitable for use by a virtual machine, for example, the code stream 202 and a Java data stream 204. Referring now to Fig. 4, an exemplary bytecode stream generation method 400 for generation of an enhanced bytecode representation is disclosed. The bytecode stream generation can be used, for example, to generate a pair of bytecode streams from a conventional Java bytecode stream 150 of Fig. 1. Initially, at operation 402, the next bytecode representing a command is read. Next, at operation 404, a bytecode representing the command is written into an entry of a code stream, for example, the Java code stream 202 of Fig. 2. Following operation 404, a determination is made at operation 406 as to whether the command has an associated parameter. If it is determined at operation 406 that the command does not have any associated parameters, the bytecode stream generation method 400 proceeds directly to operation 410 where a determination is made as to whether there are more bytecodes to read. If there are no more bytecodes to process, the bytecode stream generation method 400 ends. However, if there is at least one more bytecodes to read, the bytecode stream generation method 400 proceeds to operation 402 where the next bytecode representing a command is read.

On the other hand, when it is determined at operation 406 that the command has associated parameters, the bytecode stream generation method 400 proceeds to operation 408 where the associated parameters are read and processed. As will be appreciated, the processing of the associated parameters can be performed based on the command type in accordance with one aspect of the invention. This processing will be further illustrated in Fig. 5 below. After appropriate processing of associated parameters, at operation 409, an appropriate value is written to a data stream, for example, the Java data stream of Fig. 2. Next, the bytecode stream generation method 400 proceeds to operation 410 where a determination is made as to whether there are more bytecodes to read. if there is at least one more bytecodes to read, the bytecode stream generation method 400 proceeds to operation 402 where the next bytecode

representing a command is read. However, if there are no more bytecodes to process, the bytecode stream generation method 400 ends.

Fig. 5 illustrates an exemplary loading method 500 for loading bytecodes of a class file in accordance with one embodiment of the invention. For the sake of illustration, in the described embodiment, the loading is used in a Java runtime environment to load a Java class file. The class file can include various Java instructions (Java commands and associated data parameters). Typically, this would be accomplished by a Java class loader. It should be noted that in the described embodiment the Java commands are written into a Java code stream. Accordingly, the loading method 500 illustrates loading operations that can be performed to provide the corresponding Java code stream for the Java code stream.

Initially, at operation 502, a determination is made as to whether the Java command is a load constant command. If it is determined at operation 502 that the Java command is a load constant command, the loading method 500 proceeds to operation 504 where the load constant command is processed in accordance with one aspect of the invention. For example, such processing can be performed as illustrated below in Fig. 6.

On the other hand, If it is determined at operation 502 that the Java command is not a load constant command, the loading method 500 proceeds to operation 506 where a determination is made as to whether the Java command is an invoke method command. If it is determined at operation 506 that the Java command is an invoke method command, the loading method 500 proceeds to operation 508 where the invoke method command is processed in accordance with another aspect of the invention. In a preferred embodiment, the invoke method command is processed to create a reference cell which provides the information necessary to invoke the method at run time. For example, such processing can be performed as illustrated in co-pending U.S. Patent Application No. _____ (Att.Dkt.No. SUN1P809/P5500), entitled "IMPROVED FRAMEWORKS FOR INVOKING METHODS IN VIRTUAL MACHINES". Accordingly, in the described embodiment, the address of the reference cell corresponding to the invoke method command is written into the data stream.

However, If it is determined at operation 506 that the Java command is not an Invoke method command, the loading method 500 proceeds to operation 512 where a determination is made as to whether the Java command is a Jump command. If it is determined at operation 512 that Java command is a Jump
5 command, the appropriate code and data stream offsets of the Jump command are written into the data stream entry corresponding to the jump.

On the other hand, If it is determined at operation 512 that the Java command is not a jump command, the loading method 500 proceeds to operation 516 where a determination is made as to whether the Java command
10 is an instantiation command. As will be appreciated, if it is determined at operation 516 that the Java command is an instantiation command, the Constant pool information for the instantiation command can be processed at operation 518. Following operation 518, in the described embodiment, the appropriate type-descriptor is written into the data stream at operation 520. However, if it is
15 determined at operation 516 that the Java command is not an instantiation command, the loading method 500 proceeds to operation 522 where it is determined whether the Java command is a Get/Put field command.

As will be appreciated, if it is determined at operation 522 that the Java command is a Get/Put field command, the Constant pool information for the
20 instantiation command can be processed at operation 518. For example, a reference cell which provides the information necessary to execute the Get/Put field command at run time can be generated. Accordingly, following operation 524, the address of a reference cell corresponding to the Get/Put field command can be written into the data stream at operation 526. The loading method 500
25 ends if it is determined at operation 522 that the Java command is not a Get/Put field command.

Fig. 6 illustrates a processing method 600 for processing a Java Load constant command in accordance with one embodiment of the invention. The processing method 600 represents operations that can be performed, for
30 example, at operation 508 of Fig. 5. It should be noted that the processing method 600 can be used to convert a conventional representation of a Load constant command with its associated parameter (e.g., bytecodes 154, 156, and

157 of Fig 1). Accordingly, the processing method 600 can be used to represent the Load constant command and its associated parameter respectively into a Java code stream and a Java data stream, for example, the Java code stream 202 and Java data stream 204 of Fig. 2.

5 Initially, at operation 602, the first bytecode of the Constant Pool index (e.g., bytecode 156 of Fig. 1) is fetched. Next, at operation 604, the second bytecode of the Constant Pool index (e.g., byte code 157 of Fig. 1) is fetched. As will be appreciated, at operation 606, the Constant Pool index is constructed from the first and second fetched bytes. After construction of the Constant Pool
10 index, appropriate data structures of the Constant Pool are read at operation 608. Next, at operation 610, the corresponding constant value is determined based on the constant information read at operation 608. As will be appreciated, other operations can be performed, for example, if necessary, byte alignment can be performed at operation 610. Finally, at operation 612 the constant value
15 determined at operation 610 is written into a Java data stream, for example, the Java data stream 204 of Fig. 2. It should be noted that corresponding Java Load constant command is written into an appropriate entry of a Java code stream, for example, the Java code stream 202 of Fig. 2.

Fig. 7 illustrates an execution method 700 for executing a Java Load
20 Constant command in accordance with one embodiment of the invention. It should be noted that the execution method 700 can be implemented in a virtual machine in conjunction with an enhanced bytecode representation to allow more efficient run time execution of a Java Load Constant command. For example, the processing method 600 can be used to generate the bytecode
25 streams 200 having the Java code stream 202 and Java data stream 204. Accordingly, The Java Load Constant command can be stored in the code stream while the corresponding Constant parameters value are stored in the data stream.

Initially, at operation 702, the Java Load Constant command is fetched from the code stream. For example, referring back to Fig. 2, the bytecode 206 of
30 the Java code stream 206 (Java command A), representing a Java Load Constant command is fetched from the Java code stream 202. Next, at operation 704, a pointer to the Java code stream is incremented to point to the next command in

the Java code stream. Referring again to Fig. 2, a pointer to the Java code stream 206 is incremented to point to the next command in the Java code stream, namely, code stream 206 (Java command B). Following incrementing the pointer at operation 704, the execution method 700 proceeds to operation 706 where it is determined how many bytecodes corresponding to the Constant parameter value needs to be fetched from the Java data stream. As will be appreciated this determination can be made based on the Constant's type (e.g., double, integer, float, etc.). Accordingly, at operation 708, the appropriate number of bytes which correspond to the Constant parameter value are fetched.

After the appropriate constant value is fetched, at operation 710, the pointer to the data command stream is incremented to point to the appropriate position in the data stream. As will be appreciated, the pointer to the data stream can be updated based on the type of the Load constant command (i.e., based on the number of bytecodes appropriated for the data associated with the command). Finally, at operation 712, the Constant Load command is executed, for example, the appropriate Constant value command is pushed on the stack.

The many features and advantages of the present invention are apparent from the written description, and thus, it is intended by the appended claims to cover all such features and advantages of the invention. Further, since numerous modifications and changes will readily occur to those skilled in the art, it is not desired to limit the invention to the exact construction and operation as illustrated and described. Hence, all suitable modifications and equivalents may be resorted to as falling within the scope of the invention.

What is claimed is:

CLAIMS

1. A method of creating data structures suitable for use by a virtual machine to
5 execute computer instructions, the method comprising: converting a stream of
commands and data associated with the commands into a pair of streams for use
in the virtual machine, the pair of streams including a code stream that includes
the commands and a data stream that includes the data associated with the
commands in the code stream.
- 10 2. A method as recited in claim 1, wherein the code stream includes only
commands and the data stream includes only the data associated with the
commands in the code stream.
- 15 3. A method as recited in claim 1, wherein the stream that is to be converted is a
Java bytecode stream, the code stream is a Java bytecode code stream that
includes Java commands, and the data stream is a Java bytecode data stream that
includes the data associated with the Java commands in the java bytecode code
stream.
- 20 4. A method as recited in claim 1, wherein said converting of said stream
comprises:
writing a representation of a first command associated with a first
instruction into a code entry of the code stream;
25 determining whether the first command has data associated with it; and
writing a representation of the associated data or a reference to a
representation of the data associated with the first command into a first data
entry of the data stream when the command has an associated data.
- 30 5. A method as recited in claim 4, wherein the stream that is to be converted is a
Java bytecode stream, the code stream is a Java bytecode code stream that
includes Java commands, and the data stream is a Java bytecode data stream that

includes the data associated with the Java commands in the java bytecode code stream.

5

6. A method as recited in claim 4, wherein said method further comprises:
not providing a data entry in the data stream for the command when the command does not have data associated with it.

10

7. A method as recited in claim 6, wherein said method further comprises:
writing a representation of second command associated with another instruction into a second code entry of the code stream;
determining whether the second command has data associated with it;

15 and

writing a representation of the associated data or a reference to a representation of the data associated with the second command into a second data entry of the data stream when the command has associated data.

20

8. A method as recited in claim 7, wherein the stream that is to be converted is a Java bytecode stream, the code stream is a Java bytecode code stream that includes Java commands, and the data stream is a Java bytecode data stream that includes the data associated with the Java commands in the java bytecode code stream.

25

9. A method as recited in claim 8,
wherein the command and data entries can each include a number of bytecodes in the Java bytecode stream,

wherein the number of bytecodes is an integer, and

30

wherein each byte code can be one or more bytes.

10. A method as recited in claim 9, wherein the first and second entries of the code stream are adjacent to each other.

11. In an object oriented programming environment, a data structure for
5 containing computer executable commands and data associated with the computer executable commands, the data structure suitable for use by a virtual machine and comprising:

a code portion having one or more computer executable commands ;

and

10 a data stream having data corresponding to the one or more computer executable commands.

12. A data structure as recited in claim 11, wherein the code portion does not include any data associated with the computer executable commands and the
15 data portion does not include any computer executable commands.

13. A data structure as recited in claim 11, wherein the code portion is a code stream that includes Java commands represented as bytecodes, and the data portion is a code stream that includes the data associated with the Java
20 commands represented as bytecodes.

14. A data structure as recited in claim 13,

wherein the code stream and the data stream each comprise of a plurality of Java byte codes representing a Java bytecode stream,

25 wherein each Java command and data associated with that command are represented respectively in one or more bytecodes of the code stream and the data stream, and

wherein each bytecode can be one or more bytes.

30 15. A data structure as recited in claim 14, wherein the Java commands can be a load constant command, an invoke method command, a jump command, an instantiation command, or a get/put field command.

16. A method of executing computer instructions on a virtual machine, the method comprising:

- 5 fetching a command associated with a computer instruction from a code stream;
- determining whether the command has an associated parameter;
- fetching from a data stream the associated parameter of the command when said determining determines that command has an associated parameter; and
- 10 executing the command with the associated parameters after the associated parameter of the commands have been fetched.

17. A method as recited in claim 16, wherein the method further comprises:

- updating a pointer to the command stream; and
- 15 updating a pointer to the data stream.

18. A method as recited in claim 16, wherein the code stream includes Java commands represented as bytecodes, and the code stream includes data associated with the Java commands represented as bytecodes.

- 20 19. A method as recited in claim 18,
- wherein the code stream and the data stream each comprise of a plurality of Java byte codes representing a Java bytecode stream,
- wherein each Java command and data associated with each Java
- 25 command are represented respectively, in one or more bytecodes of the code stream and the data stream, and
- wherein each bytecode can be one or more bytes.

- 30 20. A method as recited in claim 19, wherein the Java commands can be a load constant command, an invoke method command, a jump command, an instantiation command, or a get/put field command.

21. A method of creating data structures suitable for use by a virtual machine to execute Java instructions, the method comprising:

converting a Java bytecode into a pair of Java bytecode streams suitable for use by the virtual machine, the pair of Java bytecode streams having a Java code stream that includes Java commands and a Java data stream that includes the data associated with the commands included in the code stream

22. A method as recited in claim 21, wherein said converting of said stream comprises:

writing a representation of a first command associated with a first instruction into a code entry of the code stream;

determining whether the first command has associated data; and

reading the associated data from a Constant Pool when the command has an associated data;

processing the associated data from the Constant Pool the associated data from the Constant Pool;

writing a representation of the associated data or a reference to a representation of the data associated after said processing of the associated data;

wherein each Java command and data associated with that Java command are represented respectively in one or more bytecodes of the Java code stream and the Java data stream, and

wherein each bytecode can be one or more bytes.

23. A method as recited in claim 22, wherein said processing operates to determine a constant value associated with a Java Load Constant command.

24. A method as recited in claim 22, wherein said processing operates to determine a reference to a method invocation cell that includes information relating to a Java invoke method command.

25. A method as recited in claim 22, wherein said processing operates to determine the code stream offset and data stream offset associated with a Java Jump command.

5 26. A method as recited in claim 22, wherein said processing operates to process a Constant Pool associated with a Java instantiation command.

27. A method as recited in claim 22, wherein said processing operates to process a Constant Pool associated with a Java Get/Put field command.

10

28. A method as recited in claim 22, wherein said processing operates to process data associated with a Java load constant command, a Java invoke method command, a Java jump command, a Java instantiation command, or a Java get/put field command.

15

IMPROVED FRAMEWORKS FOR LOADING AND EXECUTION OF OBJECT-BASED PROGRAMS

5

ABSTRACT OF THE DISCLOSURE

Improved frameworks for loading and execution of portable, platform independent programming instructions within a virtual machine are described. The improved frameworks provides a mechanism that will generally improve the runtime performance of virtual machines by eliminating the need to always
10 traverse a constant pool at runtime to execute a Java instruction. In addition, specific data structures that are suitable for use within a virtual machine and methods for creating such data structures are described. Accordingly, an enhanced Java bytecode representation having a pair of Java bytecode streams is disclosed. The enhanced Java bytecode has a Java code stream suitable for
15 storing various Java commands as bytecodes within a code stream. A Java data stream of the enhanced Java bytecode representation is used to store the data parameters associated with the Java commands in the code stream. Actual parameter values, or references to actual parameter values can be provided in the data stream. Thus, data parameters can be provided for efficient execution of
20 Java instructions without requiring further processing of Constant Pool at run time. As a result, the performance of Java complaint virtual machine can be enhanced.

Constant Pool Section to Reference A Method

10:	class_index=11, name_type_index=12	CONSTANT_Methodref
11:	name_index=13	CONSTANT_Class_info
12:	name_index=14, decription_index=15	CONSTANT_NameAndType
13:	length, pointer to class name string	CONSTANT_Utf8_info
14:	length, pointer to method name string	CONSTANT_Utf8_info
15:	length, pointer to signature string	CONSTANT_Utf8_info
16:		

Fig. 1A

ADD Command <u>152</u>
ICONST Command <u>154</u>
CP_IndexA <u>156</u>
CP_Index B <u>157</u>
Invoke Method Command <u>158</u>
CP_Index C <u>160</u>
CP_Index_D <u>162</u>

150
↙

Fig. 1B




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7

DECLARATION AND POWER OF ATTORNEY FOR ORIGINAL U.S. PATENT APPLICATION

Attorney's Docket No. SUN1P814/P5417

As a below-named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe that I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled: **IMPROVED FRAMEWORKS FOR LOADING AN EXECUTION OF OBJECT-BASED PROGRAMS** the specification of which,

- (check one)
1. ☒ is attached hereto.
 2. ☐ was filed on _____ as
U.S. Application No. _____
and was amended on _____.
 3. ☐ was filed on _____ as
International PCT Application No. _____
and was amended on _____.

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, CFR § 1.56.

Prior Foreign Application(s)

I hereby claim foreign priority benefits under Title 35, United States code, § 119(a)-(d) or § 365(b) of any foreign application(s) for patent or inventor's certificate, or § 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed:

			Priority Benefits Claimed?
			Yes ___ No ___
_____ (Application No.)	_____ (Country)	_____ (Filing Date)	
_____ (Application No.)	_____ (Country)	_____ (Filing Date)	Yes ___ No ___

Provisional Application(s)

I hereby claim the benefit under 35 U.S.C. §119(e) of any United States provisional application(s) listed below:

_____ (Application No.)	_____ (Filing Date)
_____ (Application No.)	_____ (Filing Date)

Prior U.S. Application(s)

I hereby claim the benefit under Title 35, United States Code, § 120 of any United States application(s), or § 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, § 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application:

_____ (Application No.)	_____ (Filing Date)	_____ (Status - patented, pending, abandoned)
----------------------------	------------------------	--


_____ (Application No.)	_____ (Filing Date)	_____ (Status - patented, pending, abandoned)
----------------------------	------------------------	--

Power of Attorney

And I hereby appoint the law firm of **Beyer Weaver & Thomas, LLP** and all practitioners who are associated with the Customer Number 022434 as my principal attorneys to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith.

Direct Correspondence To:

Customer Number: 022434
BEYER WEAVER & THOMAS, LLP
 P.O. Box 778
 Berkeley, CA 94704-0778

**Direct Telephone Calls To:**

Ramin Mahboubian at telephone number (650) 961-8300

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

Typewritten Full Name of

Sole or First Inventor: Stepan Sokolov **Citizenship:** Ukraine

Inventor's signature: [Signature] **Date of Signature:** 10/30/2000

Residence: (City) Fremont **(State/Country)** CA/USA

Post Office Address: 34832 Dorado Common, Fremont, CA 94555

Typewritten Full Name of

Second Inventor: David Wallman **Citizenship:** Israel

Inventor's signature: [Signature] **Date of Signature:** 10/31/2000

Residence: (City) Sunnyvale **(State/Country)** CA/USA

Post Office Address: 777 S. Mathilda Ave., #266, Sunnyvale, CA 94087